





SALIENT FEATURES

- " Rugged and compact design, thick rubber protective cover, Light weight
- [°] 2 in 1 Survey Meter and Dosimeter
- " Large TFT LCD with backlight for outdoor readability
- ["] Internal memory to store 60 hours to continuous data measurements

APPLICATIONS

- " Nuclear Power Industry
- " Radiography
- [®] Radiation Protection
- " Environmental Survey / Health Physics Labs
- " Civil / Defense
- " Industrial

SCOPE

- ^m DSM series are rugged and light weight instruments designed for quick and reliable gamma & Xray doserate and dose measurement.
- " It serves the functions of both Dose rate and Dose meter in single device. Separate alarm thresholds are available for Dose rate and Dose.
- " Easy menu driven interface.
- [•] Audible and visual alarm indication is given by Red LED and Buzzer.
- " It saves data of Doserate and dose continuously with Date and Time stamp. Data can be viewed by PC Software through USB Communication.

SPECIFICATION

	DSM - 1	DSM - 10i	
GeM ID	5116877-51193423831	5116877-72889202125	
DETECTOR USED	Internally Mounted Energy Compensated GM Tube		
RADIATION DETECTION	gamma & X-ray		
ENERGY DETECTION RANGE	48 KeV to 3 MeV		
DOSE RATE RANGE	0.01 mR/h to 1 R/h	0.1 mR/h to 10 R/h	
	0.1 µSv/h to 10 mSv/h	1 µSv/h to 100 mSv/h	
	0.1 µGy/h to 10 mGy/h	1 µGy/h to 100 mGy/h	
DOSE RANGE	0.01 mR to 1000 R		
DOSE RATE LINEARITY	± 15% with Co60		
DISPLAY UNITS	R/h, Sv/h, Gy/h, rem, CPS, CPM		
DISPLAY	2.8" Graphic TFT		
ALARMS	User Configurable Audio and Visual Alarm through the entire range. OL - Over load OR - Over range DET - Detector Fail EHT - High Voltage Fail		
DATA STORAGE	60 hours / 4000 data points of storage of Dose Rate with timestamp which can be read through PC Software and accumulated dose		
OPERATION TIME	100 Hours		
BATTERY	4 AAA batteries (Alkaline or Rechargable)		
OPERATING TEMPERATURE	-10°C to 50°C		
CONSTRUCTION	ABS Plastic		
WEIGHT	235 gm with batteries		
DIMENSION	76 mm x 27 mm x 135 mm		
COMMUNICATION	Micro USB		
PC SOFTWARE	RadMan PC Software		
	Silicone Cover		
	Carry Case		
	USB Cable for PC communication		
STANDARD ACCESSORIES	4xAAA Alkaline Batteries		
	USB Pendrive for PC communication with user manual		
	RadMan PC Sc	RadMan PC Software License	
	Wrist Strap		
ORDER CODE	VNIM0055	VNIM0016	

OPTIONAL ACCESSORIES

Optional Accessories	Order Code
Shock-Proof Silicone Case for Survey meter	VNIA0095
4 x AAA Rechargable Battery + Charger	VNIA0098
Extended Warranty for 2 Years	VNF2A014





AT GLOBAL TECH

San Jose, CA, USA |+1 408 772 9960 sales@atglobaltech.com